

Incredible **100,000 hrs**

GENERAL DESCRIPTION

Neptun's Induction flood fixtures features classic form and durability to make it an excellent choice for new construction or retrofit applications. The 331 series flood uses a fully adjustable slip fitter or yoke bracket mounting arm and a variety of wattages to provide flexibility in all types of applications. It can replace existing HID & HPS fixtures up to 250W.

APPLICATION

- Building Accent Lighting
- Landscape Lighting
- Sign Lighting
- Flag Pole Lighting
- Security Lighting
- Area Lighting

STRUCTURE, MATERIALS, & FEATURES

- Heavy-gauge, die-cast aluminum housing.
- Anodized aluminum reflectors for superior illuminance.
- Heat and impact resistant, tempered, flat glass lens.
- Slip Fitter or Yoke bracket mounting to allow for adjustable tilt.
- Corrosion resistant electrocoat grey finish (custom colors available).
- Hinged aluminum door frame incorporates stainless steel hardware.
- Continuous silicone gasketing surrounds lens for weather - tight seal.
- Inductively coupled rectangle induction bulb.
- High power factor, low THD electronic ballast with surge protection.
- Instant-On flicker-free Cold Start and Hot Re-Start.
- High quality glare-free light with high CRI above (83).
- Bright white light (5000°K) for greater visibility and safety.
- Advance phosphors for high lumen output and high lumen maintenance.
- Up to 20 year maintenance free operation.
- 10 Year Warranty.

ORDERING INFORMATION

Sample Number: 331040-UNV-SF-850-LD-BRZ
Custom options and accessories available. Please consult factory

Series	Lamp Wattage	Voltage	Mounting	Color Temp	Accessories	Color
331 = Flood Light	040 = 40 W 080 = 80 W 100 = 100 W 120 = 120 W	UNV = 120-277 VAC	SF = Slip Fitter YK = Yoke Bracket	830 = 3000°K 841 = 4100°K 850 = 5000°K* * Standard	LD = Light Detector/Photocell MD = Motion Sensor Detector	BRZ = Dark Bronze * Custom Colors Available



lightinnovations@work™


PRODUCT INFORMATION

Model No.	Description	Rated Watts	Input Watts	Initial Lumens	Universal Line Voltage (VAC)	Max Line Current (Amp) @ 120 - 277	THD	Power Factor	Weight
331040-UNV	Flood Fixture	40	41	3,200	120-277	0.34-0.15	<10%	0.98	18 lbs
331080-UNV	Flood Fixture	80	82	6,800	120-277	0.69-0.30	<10%	0.98	18 lbs
331100-UNV	Flood Fixture	100	105	8,000	120-277	0.87-0.37	<10%	0.98	18 lbs
331120-UNV	Flood Fixture	120	125	9,600	120-277	1.05-0.45	<10%	0.98	18 lbs


SPECIFICATIONS

- Ballast Type Electronic
- Start Method InstantON
- Hot Re-start InstantON
- Universal Input Line Voltage 120-277 VAC
- Input Line Frequency 50/60 Hz
- Lamp Operating Frequency 250 kHz
- Ballast Off-State Draw 0 Watts
- Sound Rating Class A
- ANSI Surge Protection Class A
- Lamp / Ballast System Life 100,000 Hrs.
- Lumen Maintenance @75,000Hrs > 70%
- Color Temperature 5000°K
- Color Rendering Index (CRI) 83
- Minimum Starting Temperature -20°F
- Maximum Starting Temperature 160°F
- Lumens per Watt 80
- Shock / Vibration Resistant Yes
- Power Factor > 0.98
- Total Harmonic Distortion < 10%
- Inrush Current Peak < 10 Amp
- ETL Listed / UL Standard 1598 Yes
- FCC Compliance Part 18, Subp. C
- IP Rating IP65
- Warranty 10 Year

MOUNTING OPTIONS



PHOTOMETRICS (See Complete IES File)



Type V Distribution

Neptun Light, Inc.
13950 Business Center Drive
Lake Forest, IL 60045
Fax: 847.735.8004

Neptun Light, Inc. reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.
©2002-2013 Neptun Light, Inc. All rights reserved. Spec. Rev. 1-2013