

# ECOSTAR

## Refrigeration Lighting

### PRODUCT DESCRIPTION

EcoStar ESRP-3 is a refrigeration display lighting solution designed with advanced LED and lens technologies. Offering superior, evenly-dispersed light output while using less power than conventional methods and other competing LED brands, EcoStar ESRP-3 sets the standard in quality and value. Custom lens types in 4" and 10" depths match the position in the refrigerator case (i.e. Center or End), directing light where it is needed. Combined with three color temperature options and the ability to dim through an occupancy sensor, EcoStar ESRP-3 makes it easy to create the ideal look and feel.

### PERFORMANCE SUMMARY

- EFFICACY: 52 Lm/W
- CRI: 85 min
- LIFETIME: Minimum 80,000 hours
- CCT: 3000K, 4000K, 5000K
- INPUT VOLTAGE: 24V DC
- RATING: Dry and damp locations
- DIMMING: Supports dimming through an occupancy sensor
- OPERATING TEMP: -20° to 30°C / -4° to 86°F
- WARRANTY: 5 Years



Part Number	Depth	Length/ Position	Color Temp 3000K				Color Temp 4000K/5000K			
			Lumens	Lm/ft	W/ft	Lm/W	Lumens	Lm/ft	W/ft	Lm/W
ESRP-3-1-4-24-4-50-D10-C	4"	4' Center	1000	250	5	50	1000	250	5	50
ESRP-3-1-4-24-4-50-D10-L/R		4' End	680	170	3.3	52	680	170	3.3	52
ESRP-3-1-4-24-5-50-D10-C		5' Center	1250	250	5	50	1250	250	5	50
ESRP-3-1-4-24-5-50-D10-L/R		5' End	850	170	3.3	52	850	170	3.3	52
ESRP-3-1-4-24-6-50-D10-C		6' Center	1500	250	5	50	1500	250	5	50
ESRP-3-1-4-24-6-50-D10-L/R		6' End	1020	170	3.3	52	1020	170	3.3	52
ESRP-3-1-10-24-4-50-D10-C	10"	4' Center	1000	250	5	50	1000	250	5	50
ESRP-3-1-10-24-4-50-D10-L/R		4' End	680	170	3.3	52	680	170	3.3	52
ESRP-3-1-10-24-5-50-D10-C		5' Center	1250	250	5	50	1250	250	5	50
ESRP-3-1-10-24-5-50-D10-L/R		5' End	850	170	3.3	52	850	170	3.3	52
ESRP-3-1-10-24-6-50-D10-C		6' Center	1500	250	5	50	1500	250	5	50
ESRP-3-1-10-24-6-50-D10-L/R		6' End	1020	170	3.3	52	1020	170	3.3	52



Product specifications subject to change. Visit USLED.com to find the most up to date information.